



M-CUBE+SE

M-CUBE+SE 5.1 HOME THEATRE

Continuing the success of the **M-CUBE series** we, at **Mission**, bring to you this latest version which is sure to be a favorite. This is the all-new **M-CUBE+SE** 5.1 home theatre from the innovative **M-CUBE** range.

The **M-CUBE+SE** is designed specifically to meet the requirements of the home user who requires a fuss-free solution to Cinema and Surround Sound music in the home. Installation is simple thanks to the small, elegant appearance of the **M-CUBE+SE** satellite speakers, the multiple mounting arrangements, and the wide dispersion characteristics.

SPECIFICATIONS


ITEM	M-CUBE+SE SATELLITE
General Description	Wide bandwidth bookshelf/surround speaker
Transducer Driver	3" full range
Recommended Amplifier Power	85dB
Nominal Impedance	40-80W
Minimum Impedance	4 Ohms
Frequency Response (+/-3dB)	3,6 Ohms
Bass Extension(-6dB)	120Hz-20KHz
Dimension (H x W x D)mm	100 x 100 x 103mm (packed in a system, incl. subwoofer and 5pcs satellite speakers)
Net Weight	12kg (packed in a system, incl. subwoofer and 5pcs satellite speakers)
Finish Color	Graphite black & ivory

ITEM	M-CUBE+SE SUBWOOFER
General Description	Active closed-box subwoofer system
Transducer Complement	1*8 inch (200mm) long throw bass driver
Input Sensitivity	200 mV for maximum output
Amplifier Power Output	70W
Peak Power Output	150W
Peak	110dB
Frequency Response	40Hz - 150Hz
Bass Extension (-6dB)	35Hz
Crossover Frequency	35Hz - 150Hz
Signal-to-noise Ratio(S/N)	>85dB
Special Features	Phase inversion, auto on /off, low pass filter frequency adjustment
Dimension (H x W x D)mm	(298+30) x 268 x 294mm
Net Weight (kg)	12kg (packed in a system, incl. subwoofer and 5pcs satellite speakers)
Finish Color	Graphite black & ivory



SUBWOOFER SERIES

Active Dynamic Drive Subwoofer



10" Subwoofer
200W Amplifier



12" Subwoofer
300W Amplifier

Model	LX-10SUB MKII	QX-12SUB MKII
Drive Units	1 x (10") 250mm PP cone long-throw	1 x (12") 300mm cone long-throw
Frequency Response	40 - 120Hz 33dB	35 - 120Hz 33dB
Amplifier Power Output	200W	300W
Peak Power Output	350W	450W
Line Input Sensitivity	200mV for maximum output	200mV for maximum output
Crossover Range	30 - 150Hz	30 - 150Hz
Inputs	Stereo line in (2 x RCA phono) Mono (LFE) line in (RCA phono)	Stereo line in (2 x RCA phono) Mono (LFE) line in (RCA phono)
Input Impedance	Line input 10kΩ LFE 5kΩ	Line input 10kΩ LFE 5kΩ
Signal-to-noise Ratio (s/n)	≥85dB	≥85dB
Avg. Max Output @1m	118dB	118dB
Features	Phase inversion, auto on-off	Phase inversion, auto on-off
Dimensions	Height: (412+35)mm (with feet) Width: 312mm Depth: (392+15)mm	Height: (420+58)mm (with feet) Width: 400mm Depth: (450+15)mm
Net Weight	16kg	23kg
Finishes Available	Walnut pearl, lux white, lux black	Walnut pearl, lux white, lux black

SUBWOOFER SERIES

Active Dynamic Drive Subwoofer



12" Subwoofer
300W Amplifier



15" Subwoofer
400W Amplifier

Model	ZX-12SUB	MS-450SUB
Drive Units	1 x (12") 300mm cone long-throw	1 x (15") 380mm cone long-throw
Frequency Response	35 - 120Hz 33dB	30 - 120Hz 33dB
Amplifier Power Output	300W	450W
Peak Power Output	450W	850W
Line Input Sensitivity	200mV for maximum output	200mV for maximum output
Crossover Range	30 - 150Hz	30 - 150Hz
Inputs	Stereo line in (2 x RCA phono) Mono (LFE) line in (RCA phono)	Stereo line in (2 x RCA phono) Mono (LFE) line in (RCA phono)
Input Impedance	Line input 10kΩ LFE 5kΩ	Line input 10kΩ LFE 5kΩ
Signal-to-noise Ratio (s/n)	≥85dB	≥85dB
Avg. Max Output @1m	118dB	124dB
Features	Phase inversion, auto on-off	Phase inversion, auto on-off
Dimensions	Height: (420+58)mm (with feet) Width: 400mm Depth: (450+15)mm	Height: (530+58)mm (with feet) Width: 460mm Depth: (530+15)mm
Net Weight	23kg	33kg
Finishes Available	Hi-gloss black, hi-gloss white	Black wood vinyl, walnut, rosewood, white sandex