



VAN MEDEVOORT

PH360

PHONO PRE AMPLIFIER



Features:

- Stereo phono pre amplifier
- For MM and MC cartridges
- Switchable gain and impedance
- Excellent transient response
- Very musical performance, extreme low distortion
- Audiophile components, special film capacitors
- vM Silver Cable wiring
- Gold plated relays contacts and connectors
- Silver / black finished front plate

The Van Medevoort PH360 stereo phono pre amplifier is built with very fast discrete class "A" line stages. Completely symmetrical and double differential designed with bi-polar semi conductors. With the XLR balanced outputs, this handles the most optimal connection between phono cartridge and control amplifier, but also a very musical reproduction quality for each kind of music. With jazz, pop and classical this results in a most realistic dynamics, focus and spaciousness. Input impedance and amplification are settable by front switches. The housing is extremely strong built with a nice finish. Internally provided with a stabilized power supply for direct connecting to the mains. Optional deliverable with vM Silver Cables, signal and/or mains.

Specifications:

Amp channels	2
Input impedance MC / MM	100-1000 / 10-100 Ohms / 47kOhms
Input voltage	0.3 mV / 3.0 mV - 1 kHz
RIAA control	< 0.3 dB
Signal / noise ratio	-83 dB / -93 dB
Bandwidth	1 Hz - 100 kHz
Channel separation	> 91 dB
Gain	60 dB / 40 dB - 1 kHz
Subsonic filter	6 Hz / -3 dB
Power supply	115-230 Volt / 50-60 Hz
Power consumption	25 Watt
Weight	8.5 kg
Size b x h (h+feet) x d	434 x 88 (102) x 395 mm

Options: vM Silver Cable

Van Medevoort
Audio products

Visit our website for more information.
Copyright © 2018 Van Medevoort Audio / Netherlands
Specifications are subject to change without prior notice.

www.vanmedevoortaudio.nl
contact@vanmedevoortaudio.nl