



VAN MEDEVOORT

PA471

MONO POWER AMPLIFIER



Features:

- 450 Watt mono music power
- Handles any loudspeaker system including ESL
- Excellent transient response through high slew rate
- Outstanding musical performance with low distortion
- XLR and RCA gold plated input connectors
- Protection circuitry and muting
- Remote controlled on / off by way of DC bus
- Silver or black finished front plate

The Van Medevoort PA471 mono class 'A' power amplifier is built with very fast, low-distortion, discrete power stages and an oversized power supply section for the most musical performance and best control over your loudspeaker system under any load, and with any kind of music. The housing is extremely solid with a beautiful finish in silver or black. Only high-grade audiophile components and Silver Wire are used. A 12 Volt DC input is installed to switch the PA471 on and off with the remote control bus of your vM control amplifier.

Specifications:

Nominal power	> 1x 450 Watt / 8 Ohms
Damping factor	1200 - 1500
Input impedance	100 kOhms
Input level	1.5 Veff. / 450 Watt
Distortion	< 0.002 % / 1 -100,000 Hz
Signal to noise ratio	> 106 dB
Inputs / connectors	1 / XLR + RCA switchable
Outputs / connectors	1 / 5 way binding post
Power supply	115-230 Volt / 50-60 Hz
Power consumption	5/60-550 Watt stb/min-max.
Weight	14 kg
Size w x h (h+feet) x d	434 x 88 (102) x 410 mm

Options: vM Silver Cable

Van Medevoort
Audio products

Visit our website for more information.
Copyright © 2015 Van Medevoort Audio / The Netherlands.
Specifications are subject to change without prior notice.

www.vanmedevoortaudio.nl
contact@vanmedevoortaudio.nl